

UNCLASSIFIED

AD 410865

DEFENSE DOCUMENTATION CENTER

FOR

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERON STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

N-63-4-3

⑤ 659 050

①

OFFICE OF NAVAL RESEARCH

Contract Nonr 2687(00),

Task No. NR 356-408,

AD 410865

File Copy

④ TECHNICAL REPORT NO. 37

⑥ New High Pressure Form of Calcium Disilicide,

⑩ by

M. S. Silverman and J. R. Soulen.

Accepted by the Journal of Physical Chemistry

PENNSALT CHEMICALS CORPORATION
Research and Development Department
Wyndmoor, Pennsylvania

June 1963

Reproduction in whole or in part is permitted for
any purpose of the
United States Government

410865

④
\$ 1.10

JUL 31 1963

NEW HIGH PRESSURE FORM OF CALCIUM DISILICIDE

By M. S. Silverman and J. R. Soulen

Research and Development Laboratories

Pennsalt Chemicals Corporation

Wyndmoor, Pennsylvania

Calcium disilicide is known to have a hexagonal layer type structure¹ as do graphite and boron nitride. At very high pressures and

(1) J. Böhm and O. Hassel, Z. anorg. u. allgem. Chem., 160, 152 (1927).

temperatures the latter compounds form the more dense cubic polymorphs, diamond² and borazon.³ CaSi_2 has ~~now~~ been transformed at high

(2) F.P. Bundy, H. T. Hall, H. M. Strong, and R. H. Wentorf, Jr., Nature, 176, 51 (1955).

(3) R. H. Wentorf, Jr., J. Chem. Phys., 26, 956 (1957).

pressures to a new, more dense modification which appears to be tetragonal.

Commercial grade CaSi_2 obtained from K and K Laboratories was used as one starting material. This contained several percent iron

as an impurity. Mixtures of semiconductor grade silicon, spectroscopic grade graphite, and CaO prepared by heating 99.9 % CaCO_3 were also used.

The apparatus was of the tetrahedral anvil type developed at the National Bureau of Standards.⁴ The sample holder, heating

(4) E. C. Lloyd , U. O. Hutton and D. P. Johnson, J. Res. N. B. S., 63C, 59 (1959).

assembly, and calibration techniques were similar to those described previously,⁵ except that a boron nitride insulating capsule was used

(5) J. R. Soulen and M. S. Silverman, J. Polymer Sci., 1, 823 (1963).

between the graphite heater and the sample.

In carrying out the runs, CaSi_2 or a $\text{CaO} + \text{Si} + \text{C}$ mixture was first compressed to the desired pressure between 8 and 87 kilobars, temperature was then raised and held at the desired level, which ranged up to 1800° . After 2 to 10 minutes the electrical power was shut off and the sample was decompressed after the product had reached ambient temperature.

With CaSi_2 as the starting material, striking changes were noted in the solid resulting from a number of runs. Under microscopic examination it appeared

that essentially 100% conversion to a reflective, coral material had occurred from the original grey form. In concentrated HCl the latter reacted with vigorous effervescence whereas the new form, even when finely ground, underwent only slight reaction. Density of the hexagonal starting material was $2.47 \pm 0.02 \text{ g/cm}^3$, in good agreement with 2.46 g/cm^3 reported previously.¹ Measured densities of the high pressure form ranged from 2.60 to $2.76 \pm 0.02 \text{ g/cm}^3$. The highest value was obtained from a product formed under the most severe combination of conditions, 87 kilobars and 1500° , and thus must be closest to correct for the new form. X-ray diffraction films of many of the samples gave an identical powder pattern which is characteristic of the new form and is completely different from that of the original material. The strongest lines are listed in Table I.

These can be indexed on the basis of a tetragonal structure with $a = 6.23 \text{ \AA}$ and $c = 4.52 \text{ \AA}$. Density calculated from these constants, assuming 3 CaSi_2 per unit cell, is 2.73 g/cm^3 , compared with 2.76 for the highest density product. Taking the iron impurity into account, product analysis showed about 2.6% Fe, and a composition approximately $\text{Ca}_{0.93}\text{Fe}_{0.05}\text{Si}_{2.00}$. Assuming simple substitution of Fe for Ca to this extent in the proposed CaSi_2 structure, calculated density is 2.75 g/cm^3 , in excellent agreement with the measured value.

To determine whether iron is a necessary constituent of the new structure, reaction of calcium oxide, silicon and carbon was carried out under high pressure conditions using very pure reactants. Although conversions were poor, the X-ray diffraction powder pattern of Table I was obtained from a number of the pressed pellets, showing formation of the new high pressure form from these entirely different reactants in which the impurity level is very low. The pattern must thus be characteristic of calcium disilicide itself, and the presence of iron in the products obtained from impure CaSi_2 is not essential to obtain it.

The high pressure form was obtained from hexagonal CaSi_2 in varying amounts over the ranges 17 to 87 kilobars and 700° to 1800° . Below 17 kilobars no transformation occurred, even at temperatures up to 1500° . Besides thermodynamically favoring the reaction, pressure also favors formation of the new form kinetically. Thus in 10-minute runs at 1250° and 17 and 42 kilobars, conversions to the high pressure form were less than 50% and 100%, respectively. At 1000° no new product was obtained after 10 minutes at 20 kilobars whereas complete conversion resulted after 10 minutes at 50 kilobars and 3 minutes at 83 kilobars. To obtain essentially complete conversion to the high pressure form in short periods of time, pressures above 40 kilobars and temperatures above 1000° are required simultaneously.

The authors wish to thank Dr. W. Clavan and Mr. R. Hamilton for obtaining the X-ray diffraction patterns, and the analytical


and shop groups for their help in this work. It was supported in part by the Office of Naval Research.

TABLE I. X-RAY POWDER DIFFRACTION PATTERN OF HIGH PRESSURE
FORM OF CALCIUM DISILICIDE

$d(\text{\AA})^a$	I	hkl	$\sin^2 \theta$	
			obsd.	calc. ^b
2.77	100	210	.0774	.0766
2.28	80	002	.1143	.1164
2.14	55	102	.1297	.1317
1.76	55	212	.1918	.1929
1.56	50	$\left\{ \begin{array}{l} 222 \\ 400 \end{array} \right.$.2442	$\left\{ \begin{array}{l} .2388 \\ .2450 \end{array} \right.$
1.512	30	$\left\{ \begin{array}{l} 302 \\ 410 \end{array} \right.$.2599	$\left\{ \begin{array}{l} .2542 \\ .2603 \end{array} \right.$
1.326	30	$\left\{ \begin{array}{l} 213 \\ 421 \end{array} \right.$.3380	$\left\{ \begin{array}{l} .3387 \\ .3353 \end{array} \right.$
1.235	25	223	.3896	.3843

a Copper K_{α} radiation taken as 1.5418 \AA .

b Assuming tetragonal structure with $a = 6.23 \text{ \AA}$ and $c = 4.52 \text{ \AA}$.



TECHNICAL REPORT DISTRIBUTION LIST

Pennsalt Chemicals Corporation

Contract No. Nmr 2687(00)		NR 356-408	
No. of Copies		No. of Copies	
(1)	Commanding Officer Office of Naval Research Branch Off. The John Crerar Library Building 86 East Randolph Street Chicago 1, Illinois	(1)	U.S. Army Chemical Research and Development Laboratories, Technical Library Army Chemical Center, Maryland
(1)	Commanding Officer Office of Naval Research Branch Off. 346 Broadway New York 13, New York	(1)	Office of Technical Services Department of Commerce Washington 25, D.C.
(1)	Commanding Officer Office of Naval Research Branch Off. 1030 East Green Street Pasadena 1, California	(1)	Dr. P. A. Miller Office of Naval Res. Br. Off. 1000 Geary Street San Francisco 9, California
(7)	Commanding Officer Office of Naval Research Branch Off. Box 39 Navy #100 Fleet Post Office New York, New York	(1)	Dr. C. Haber Naval Ordnance Laboratory Corona, California
(6)	Director, Naval Research Lab. Washington 25, D.C.	(1)	Dr. Porter W. Erickson Chemistry Research Department Non-Metallic Materials Division Room 4-171 Naval Ordnance Laboratory White Oak, Maryland
(2)	Attn: Technical Information Officer Chemistry Division	(1)	Dr. Albert Lightbody Naval Ordnance Laboratory White Oak, Maryland
(10)	Chief of Naval Research Department of the Navy Washington 25, D.C. Attn: Code 425	(1)	Naval Ordnance Test Station China Lake, California Attn: Head, Chemistry Division Code 40 Code 50
(1)	Technical Director Research & Eng'g. Division Off. of the Quartermaster Gen'l Department of the Army Washington 25, D.C.	(1)	Commanding Officer and Director U.S. Naval Civil Engineering Lab. Port Huene, California Attn: Chemistry Division
(1)	DDR&E Technical Library Room 3C-128, The Pentagon Washington 25, D.C.	(1)	Dr. A. L. Powell Office of Naval Research Br. Off. 495 Summer Street Boston 10, Massachusetts
(1)	Research Director Clothing & Organic Materials Division Quartermaster Research & Engineering Command U. S. Army Natick, Massachusetts	(1)	Aeronautical Systems Division ASRCNP Wright-Patterson Air Force Base Ohio
(1)	Air Force Off. of Scientific Res. (SRC-E) Washington 25, D.C.	(1)	Director, Naval Research Lab. Washington 25, D.C. Attn: Code 6120, Attn: Dr. R. B. Fox Code 6120, Attn: Mr. J.E. Cowling Code 6120, Attn: Dr. A.L. Alexander Code 6120, Attn: Dr. D.L. Venesky Code 6210, Attn: Mr. J.A. Kies Code 6110, Attn: Mr. E.J. Kohn
(1)	Commanding Officer Diamond Ordnance Fuse Labs. Washington 25, D.C. Attn: Tech. Information Office Branch 012	(1)	Dr. H. C. Clark Department of Chemistry University of British Columbia Vancouver, British Columbia CANADA
(1)	Office, Chief of Research & Development Department of the Army Washington 25, D.C. Attn: Physical Sciences Division	(1)	Dr. E. G. Rochow Department of Chemistry Harvard University Cambridge 38, Massachusetts
(2)	Chief, Bureau of Ships Department of the Navy Washington 25, D.C. Attn: Code 342C Code 634C	(1)	Dr. H. T. Smyth School of Ceramics Rutgers - The State University New Brunswick, New Jersey
(1)	Chief, Bureau of Naval Weapons Department of the Navy Washington 25, D.C. Attn: Technical Library Code: RRMA-3	(1)	Dr. John E. Leffler Department of Chemistry Florida State University Tallahassee, Florida
(10)	ASTIA Document Service Center Arlington Hall Station Arlington 12, Virginia	(1)	Dr. William N. Lipscomb Department of Chemistry Harvard University Cambridge 38, Massachusetts
(1)	Director of Research U.S. Army Signal Research & Development Laboratory Fort Monmouth, New Jersey	(1)	Dr. T. D. Parsons Department of Chemistry Oregon State College Corvallis, Oregon
(1)	Naval Radiological Defense Lab. San Francisco 24, California Attn: Technical Library	(1)	Dr. L. F. Rahn Princeton Plastics Laboratory Princeton University Princeton, New Jersey
(1)	Stanford Research Institute Menlo Park, California Attn: Mr. Maurice L. Huggins	(1)	Dr. A. V. Tobolsky Department of Chemistry Princeton University Princeton, New Jersey
(1)	Commanding Officer Army Research Office Box CM, Duke Station Durham, North Carolina Attn: Scientific Synthesis Office	(1)	Dr. R. S. Stein Department of Chemistry University of Massachusetts Amherst, Massachusetts
(1)	Brookhaven National Laboratory Chemistry Department Upton, New York	(1)	Dr. Hans B. Jonasson Department of Chemistry Tulane University New Orleans 15, Louisiana
(1)	Atomic Energy Commission Division of Research Chemistry Programs Washington 25, D.C.	(1)	Dr. Henry Taube Department of Chemistry Stanford University Stanford, California
			(over)

TECHNICAL REPORT DISTRIBUTION LIST (Cont.)

Pennsalt Chemicals Corporation

Contract No. Nonr 2687(00)

NR 356-408

No. of Copies

Atomic Energy Commission Division of Technical Information Extension Post Office Box 62 Oak Ridge, Tennessee	(1)
Plastics Technical Evaluation Center Picatinny Arsenal Dover, New Jersey	(1)
John I. Thompson & Co. 1118 -22nd St., N.W. Washington, D.C. Attn: Mr. Carl A. Posey	(1)
Dr. M. S. Cohen, Chief Propellants Synthesis Section Reaction Motors Division Denville, New Jersey	(1)
Dr. M.J.S. Dewar Department of Chemistry University of Chicago Chicago 37, Illinois	(1)
Commanding Officer Ordnance Materials Res. Office Watertown Arsenal Watertown 72, Mass. Attn: RPD	(1)
Commanding Officer Rock Island Arsenal Rock Island, Illinois Attn: Mr. R. Shaw, Laboratory	(1)
Monsanto Research Corporation Everett Station Boston 49, Mass. Attn: Librarian	(1)
Dr. T. L. Heying Organics Division Olin Mathieson Chemical Corporation 275 Winchester Avenue New Haven, Connecticut	(1)
Dr. W. S. Fyfe Department of Geology University of California Berkeley, California	(1)
New York Naval Shipyard Material Laboratory Brooklyn 1, N. Y. Attn: Mr. B. B. Simms	(1)
Professor R. S. Nyholm University College London, Department of Chemistry Gower St., WCI London, England	(1)
Monsanto Research Corporation 1515 Nicholas Road Dayton, Ohio Attn: Librarian	(1)
Mr. G. W. Harding Materials Officer Defense Research Staff British Embassy 3100 Massachusetts Ave., N.W. Washington 8, D.C.	(1)
Dr. Roald Hoffman Department of Chemistry Harvard University Cambridge 38, Mass.	(1)
The Dow Chemical Co. ARPA Laboratory 1710 Building Midland, Michigan	(1)
Naval Ordnance Test Station China Lake, California Attn: Code 4544 (Dr. Kaufman) Code 5557 (Mr. S. H. Herzog- Mr. R.J. Landry)	(1) (1)